REF ID: A1051

ADÖRESS ONLY THE COMMISSIONER OF PATENTS WASHINGTON 21, D. C.

DEPARTMENT OF COMMERCE UNITED STATES PATENT OFFICE WASHINGTON

All communications respecting this application should give the serial number, date of filing name of the applicant, and

PAPER NO. 18

In re application of

Ser. No. 470,193
Filed Mar. 6, 1943
For SYSTEM FOR BRCIPMENING

Appeal No.21,161

Before the Board of Appeals

U. S. PATENT OFFICE

OCT 11 1949

MALITHE STATEFFIT

MAILED Claims 1, 2, 3, 4, 8, 9, 10, 11 and 12 have been

cancelled.

Claims 5, b, 7, 13 and 15 stand allowed.

The apposited claim is as follows:

Chair lie Means for secretly transmitting graphic infromtion comprising a device for scanning and representing said
ruphic information as a series of electric impulses of varying
line sity, a camouflage message, a second device arranged for
scanning said camouflage message and reproducing the same as a
second series of electric impulses of varying intensity the impulses
of said first series, an electromechanical interlock connected under
the control of both of said series of impulses for emergization
whosever predetermined combinations of impulses occur in the
two said series of impulses, and a transmitter controlled by said
interlock and adapted to emit impulses whenever said interlock
is energized.

REFERENCES

Verman Cartier 1,310,719

July 22, 1919 July 26, 1932

APPLICANT'S DISCLOSURE

Applicant's disclosure relates to a facsimile enciphering system.

In Fig. 1 of the drawings are shown two faceinile spanners comprising two transparent scanning drums 5 and 5 mounted for concorrent rotation. On one drum (4) is placed the message sheet which may bear any type of information such as writing, maps, draw nos, oto. In the other drum (5) is placed a ciphering sheet which may bear random patterns, writings, etc.

Approved for Release by NSA on 09-10-2013 pursuant to E.O. 13526

The light from sources 7 and 8 passing to cells 10 and 11 respectively is modulated by the information carried on the associated sheets in a conventional manner.

Dependent upon whether cells 10 or 11 are energized by the passage of light from their respective sources, relays 14 and/or 15 will be operated. If both relays tengues 16 and 17 assume the same position no energizing circuit for relay 23 will be completed. If the two tengues however, assume opposite positions a circuit will be completed through battery or source 22 to operate relay 23 and associated tingue 24. Thus the operation of relay 23 which keys transmitter 27 to emit signals is dependent upon a composite of the electrical signals generated by cells 10 and 11 in response to the subject matter on sheets 4 and 6.

Fig. 2 shows the operation of relay 25 in tabular form. For example, referring to column 1 of Fig. 2, if cell 10 is energized relay 14 will operate its tongue 16 to the left. Also if simultaneously cell 11 is deenergized spring 19 will hold tongue 17 to the right. Thus a circuit will be completed through battery 22 to energize relay 23 to cause transmitter 27 to emit a signal.

Column 2 of the chart shows the result when both relays lip and 15 are energized. In this case no circuit including the battery will be completed and therefore no signal will be transmitted.

Column 4 shows the result when both relays 14 and 15 are deenergized and the result will be the same as that of column 2.

column 3 shows the result when relay 14 is deenergized and relay 15 energized. In this condition relay 23 will operate to cause transmitter 27 to smit a signal.

The operation of the receiver need not be described since not in involved in the claim under consideration.

478,193

77

WREFERENCES*

Cartier 1,868,967--

This patent is directed to a telegraph enciphering system. The transmitter system is most clearly shown in Fig. 2 of this patent wherein are shown schematically two adjacent tape telegraph sensing units U and H. These two units are designed to operate with a conventional five-unit telegraph code wherein each character is represented by a permutation of five positive or negative impulses. Therefore for each successive message character in unit U the elements K will be moved commutatively to contact either positive bar Al or negative bar Al. A similar operation will occur in coding unit E which operates its bars Kl in accordance with a random ciphering tape.

The composite operation of bers K and Kl will control.

"interlock" relays J. For example, the lat left ber K is shown
contacting positive ber Al and the lat left ber Kl is also contacting positive ber Kl. Since both bars K, Kl are at the same
potential relay J will be in its upper position.

The next adjacent bar K is also shown in the upper position but corresponding bar K, is in the lower position. Thus a circuit through the bat any connected to bars Al and A2 is completed to cause operation of the associated relay J to the lower position in contact with bar P2 and thus apply negative potential to the associated distributor segment. The rotating brush bl sweeps the segment and distributes the pulses to the line sequential.

Vernam 1,510,719---

The Vernam patent is similar to that of Cartier. Eriefly in 11. 1 at C is shown the message transmitter and at D the cipher tape transmitter. Dependent upon the operation of the two transmitters relays 19 to 25 inclusive will be operated or not: operated so as to apply a coded message to the transmitting distillator D.

470,193

4

REJECTION

Claim lip stands rejected as being unpatentable over Cartier or Vernau. The claim is considered readable on the claim patents as foll. ws:

"Means for secretly transmitting prophic information"

Both Cartier and Vornam relate to secret telegraphy systems.

"comprising a device for scanning"

An automatic tape transmitter may be substituted for the kerboard transmitter C of Vernam. See Vernam spec. no 0., likes 01 to 97 inclusive, and lines 103 to 107 inclusive.

A tape transmitter is a "device for scanning" since it senses successive pertions of a tape.

A similar tape transmitter could be substituted for the keyboard transmitter U of Cartler because Vorman stated such a substitution was known in the art at least eight years prior to Cartler's application.

" and representing said graphic information as a series of electric impulses of varying intensity,"

The graphic information to be conveyed is translated through the medium of the tape in the transmitter into a series of impulses of varying intensity.

In Certier the intensity of the pulses varies from a magative value to a positive one as the bars K are moved either to bar Al or Al.

In Vernan the intensity of the impulse in transmitter C vary from open circuit to closed circuit, i.e. no voltage or voltage.

" a camouflago messago,"

The camouflage message is represented by the code tape in transmitter D of Vernam and transmitter N of Cartier. Vernam page 3, lines 13 to 20 inclusive and Cartier page 2, lines 55 to 67 inclusive.

"a second device arranged for scanning said carrillage message and reproducing the same as a second series of electric impulses of varying intensity"

This clause is readable on unit D of Ver am or unit N of Cartier in the same manner as has been set forth as to the first device.

"the impulsor of said second series being nonsynchronous with the impulses of said first series."

It is submitted that the operation of bars K with respect to bars Kl of Cartier for example, is "non-synchronous". Webster's New International Dictionary Unabridged 1940 Edition defines "synchronous" under the subtitle of FRYSICS as meaning-

"having the sene period and ,hase".

Each bar E can have two positions with respect to each corresponding bar El. In either position the bara El can be either positive or negative with respect to the corresponding bar E.

Therefore the impulse occurence in Cartior's system can be termed "nonsychrencus" since the pulses do not necessarily have the same phase.

The term is similarly applicable to Vernam.

It is further noted that there is no structure regited in the claim to ascribe a particular meaning to the word "nonsynch-rinous".

" an electromechanical interlock connected under control of both sories of impulses for energisation whenever predetermined combinations of impulses occur in the two said series of impulses."

The relays J of Certier and relays 19 to 23 inclusive of Vernam constitute an electromechanical interlock under control of the two series of impulses. In Cartier the relays J are controlled by bars K and Kl acting together while the relays 19 to 23 inclusive are controlled by devices C and D acting together.

-6-

" and a transmitter controlled by said interlock and adapted to emit impulses whomever said interlock is energized."

The distributor DL of Cartier and distributor A of Vernam are transmitters controlled by the interlock.

In Cartier the interlock relays J apply resulting coded signals to the acquents of the distributor DL, while in Vernam relays 19 to 23 inclusive apply the coded signals to A.

Both distributes are adapted through the rotation of their associated brushes over the segments to transmit impulses to the respective lines.

For the foregoing reasons the rejection of claim lip is believed proper and should be affirmed.

Respectfully submitted,

SaC/is

Cut Examiner, My. 16

attorney:

Henry B.Stauffer Army Security Ajency Penta on Bldg. Washington, 25, D. C.

727

ADDRESS ONLY
THE COMMISSIONER OF PATENTS
WASHINGTON, D. C.

Paper No. 19

DEPARTMENT OF COMMERCE UNITED STATES PATENT OFFICE WASHINGTON

October 31, 1949

Sir:

The case of William F. Friedman

Appeal No: 21,161

Serial No: 478,193

will be heard by the Board of Appeals on the

25th day of September 1950

The hearings will commence at 9:30 a. m. and as soon as the argument in one case is concluded, the succeeding case will be taken up.

The time allowed for argument is thirty minutes.

By special leave, obtained before the argument is 'commenced, the time may be extended.

Briefs must be filed TWENTY (20) DAYS before the day of hearing. (Rule 137, amended September 6, 1945.)

Very truly yours,

Lawrence bokingsland

Commissioner of Patents.

Refer to APPEAL NUMBER

To

Henry B. Stauffer Army Security Agency The Pentagon Washington 25, D. C.